




THE LEGACY GROWS.

Proven reliability returns. The Pierce® Enforcer™ chassis is more capable than ever. With TAK-4® independent front suspension, your choice of three powerful engines, and Pierce's exclusive Command Zone™ multiplexed electrical system, the Enforcer performs like never before.

Plus you can take advantage of significant improvements in visibility, space, ergonomics, and serviceability.



Visibility & Space

- Exceptional visibility is achieved through a large, bonded, single-piece, wrap-around windshield
- The smaller engine tunnel is lower & more contoured for increased occupant space, particularly up front for the driver & officer
- The forward roof design offers a cathedral ceiling feel with increased frontal visibility & more configurable space

Ergonomics

- Exterior door handles are functionally designed for a firefighter's gloved hand
- The steps are lower to the ground & offset to function like a stair step, making it easier for firefighters to enter & exit the cab
- The console & metal overhead switch panel are ergonomically designed for maximum convenience & comfort, keeping all of the gauges & switches within easy reach of the driver

Serviceability

- Easy access to the defroster & wiper motors through removable officer-side panels
- Power distribution relocation provides more interior space & fewer harnesses in the frame & up through the cab for easier servicing
- Built-in wire raceways throughout the cab reduce the chance of wire chafing & make it easier to service or add cab harnesses & wiring

Maneuverability

- Maximum 50 degree cramp angle & 15 degree angle of approach for improved maneuverability in those tight areas & challenging situations

Specifications

Engine	Cummins L9, X12, or Detroit Diesel DD13
Engine Horsepower	370 – 525 hp
Transmission	Allison 3,000 EVS, 4,000 EVS, or 4,500 EVS
Alternator	270 – 430 amp
Front GAWR (maximum)	24,000 lb
Front Axle Suspension	Leaf or TAK-4®
Cramp Angle (maximum)	50°
Rear GAWR (maximum)	48,000 lb
Rear Axle Suspension	Leaf, rubber, air, TAK-4, or TAK-4 T3™; single or tandem
Frame Rail	10.25"
Cab Width	96"
Cab Length	60", 70", or 84"
Cab Roof Style	Flat or raised (10" or 24")
Seating Capacity	8
Doors	Barrier or full height
Side Roll Protection	Default
Frontal Air Bags	Default
Electrical System	Hard wired or Command Zone™

www.piercemfg.com



Pierce Manufacturing Inc., An Oshkosh Corporation Company
P.O. Box 2017, Appleton WI 54912-2017 USA

Specifications, descriptions, and illustrative material in this literature are as accurate as known at the time of publication, but are subject to change without notice. Illustrations may include optional equipment and accessories and may not include all standard equipment. All measurements are nominal values.

© Pierce Manufacturing Inc., Pierce and the Pierce logo are registered trademarks and Enforcer and Command Zone are trademarks of Pierce Manufacturing Inc., Appleton, WI.

TAK-4 is a registered trademark and TAK-4 T3 is a trademark of Oshkosh Defense, LLC, Oshkosh, WI.

Printed in U.S.A.

All other trademarks are the property of their respective owners.

P-0131-ENFORCERS 12/19