

QUOTATION

SIDDONS-MARTIN EMER GROUP

Trophy Club

Siddons-Martin Emergency Group

Exp. Date: 01/03/2018
 Quote No: 10279-0001
 ULTRAMEDIC: UM1020 Ultramedic Type 1 - 168" Ford
 INFO: SPEC TERMS Road Rescue Boilerplate
 CHASSIS T1: RR-CHASF2 Ford, F-Series, 189" WB - 168" Bodies
 T1 - 168: UM-1168F Type 1 - UM 168" Module, F-Series
 EMS EQUIP: EMS-ZERO Dealer Provided - EMS Equipment

02/14/2018 09:06:47

Page 1

PART NO	S	DESCRIPTION	QTY	ID
== Road Rescue Boilerplate 1.022 11/20/17 ==				
00-01-0999		Information Scope, Purpose and Classification	1	RRI
		WARRANTY	1	RRI
00-02-8100		Warranty Documentation	1	RRI
00-02-8200		Warranty Module Structural	1	RRI
00-02-8300		Warranty Electrical, Standard System	1	RRI
00-02-8400		Warranty Paint	1	RRI
00-02-8500		Warranty Conversion	1	RRI
== Ford, F-Series, 189" WB 168" Bodies 1.022 11/20/17 ==				
01-CHASSIS REQUIREMENTS				
01-01-2508		2018 Ford F550 XLT 4X2, , 193"W/B, 19,500 GVWR (Special Order) 18-1	1	RRI
CHASSIS OPTIONS				
01-03-1001		Alternator Standard OEM	1	RRI
01-07-0110		Front Suspension Ford F-Series (4x2)	1	RRI
01-07-1000		Sway Bar, Front OEM	1	RRI
01-07-8007	<	Rear Suspension Liquid Spring-2017+ F550, 19,500 GWV	1	RRI
		Dump Feature activated by the Left rear access door. Override switch to be in right rear entry door lock box Ignition switch Hot, Standard.		
		Per KKK, the rear suspension shall only lower the module when the vehicle is in park and the parking brake is set.		
01-17-4900	<	Block Heater With OEM Plug (STANDARD) This option does not include a switch... (STANDARD).	1	RRI
CAB EXTERIOR OPTIONS				
01-19-00SR	X <	Buckstop front bumper with full wrap, black SR #2018048F Buckstop Classic 2 bumper - Black.	1	RRI
01-20-0100		Mirrors OEM Standard	1	RRI
CAB INTERIOR OPTIONS				
01-21-3500		Cab Insulation Thinsulate in Cab Ceiling (STANDARD)	1	RRI
01-22-6000		Anti-Theft Device, Secure Idle, E Series, F Series, Navi	1	RRI
TIRES / WHEELS				
01-23-4000	<	Spare Tire Bracket Installed. (STANDARD) Install Spare Tire Mounting Bracket. See drawings for location. (STANDARD)	1	RRI
01-24-2003		SS Wheel Simulators Phoenix w/ Lug Nut covers, F-Series and TerraStar	1	RRI
== Type 1 UM 168" Module, F-Series 1.022 11/20/17 ==				
00-05-0100	<	This unit built in accordance with KKK-A1822-F CN 10 This unit as specified meets all requirements of KKK-A1822-F Change notice 10.	1	RRI
		All cabinets shall be labeled as to their capacity Rating.		

PART NO	S	DESCRIPTION	QTY	ID
02 MODULE REQUIREMENTS			1	RRI
02-01-7004	< >	Ultramedic 168"L x 96"W Type 1 Module 18-1	1	RRI
		Ultramedic I - 168"L x 96"W Type I Aisle width to be 46". The interior headroom shall be 72"		
02-01-9500		Interior Headroom 72"	1	RRI
02-01-9622	>	Standard Aisle Width = 46"	1	RRI
02-02-1000		Materials, Type I & Type III	1	RRI
03 MODULE EXTERIOR			1	RRI
03-02-0200		Module Undercoating (STANDARD)	1	RRI
EXTERIOR MODULE CONSTRUCTION			1	RRI
03-03-01SR	X <	increase the width of the rear entry doors SR #2018048F increase the width of the rear intry doors to accommodate the 98 inch wide body	1	
03-03-1400	>	Module Roof Radius, 3 Inch High (STANDARD)	1	RRI
03-03-1500	>	Extreme Bonding Tape (STANDARD)	1	RRI
03-03-1600	>	Sub-floor Gusset Supports (STANDARD)	1	RRI
03-03-1700	>	One Piece Side Body Panels (STANDARD)	1	RRI
03-03-1800	>	Reinforce Rear Header (STANDARD)	1	RRI
03-03-1900	>	Single Sheet Module Roof Sheet (STANDARD)	1	RRI
03-03-2010	< >	Drop Curbside Forward Body Skirt 5", Add Double Step, Light Duty Chassis Drop Curbside Forward Body Skirt, Add Double Step ahead of the Curbside Wheelwell - Drop curbside forward body skirt a total of 5 Inches lower than the rearward skirt and Incorporate a Double Step in the Side Entry Step well. Increase the depth of stepwell inboard as far as sub structure permits. Side surfaces to be Diamond Plate. Step surface to be a combination of NFPA Diamond Plate and removable 9" Grip Strut insert. The second step to be fabricated of NFPA Diamond Plate and installed so that the step surface is midway between the stepwell floor surface and the module floor (Ultramedic, Promedic only)	1	RRI
03-03-2110	>	Drop Streetside Forward Body Skirt 5", Light Duty Chassis	1	RRI
03-03-8005		Fuel Fill Standard Pocket Square	1	RRI
03-03-8401		DEF Fill Standard Pocket, For Ford F series	1	RRI
MODULE ENTRANCE			1	RRI
03-05-0100	>	Module Access Standard	1	RRI
03-06-0100	<	Entry Doors Hidden Hinge, Seal on Door ,W/Fail Safe Latching,STD This includes the Fail Safe Latching mechanisms on all three entrance doors.	1	RRI
03-06-0700		Door Restraints Rear, Polished Cast Aluminum, Pin & Slot Style	1	RRI
03-06-0800	<	Door Restraints Side, Heavy Duty Gas Spring Hold Opens Curbside Door Restraint - Heavy Duty gas spring hold opens. - Attached by 1/4" x 20 SS Machine Screws with 1/4" x 20 Nut Inserts into Corner Gusset in Door Side entrance door to open to 90+ degrees. (STANDARD)	1	RRI
03-06-1480	<	Entry Door Handles, Trimark Chrome/Black, (Interiors relocated to top of door) ***** Relocate the Standard Interior Side and Rear Entrance Door Paddle Handles and Lock Boxes to the TOP of the doors. NOTE: This option is not available with Eberhard Handles	1	RRI
03-06-1500		Door Panel, Inner Stainless Steel (STANDARD)	1	RRI
03-06-2200		Magnetic Entry Door Switches (STANDARD)	1	RRI
03-06-4010	>	Lock Boxes, White Diamond Grade (STANDARD)	1	RRI
03-06-4200		Coil Cords for Electrical Circuits (STANDARD)	1	RRI
03-06-4400		Door Panel Mounting Screws (STANDARD)	1	RRI
03-06-9997		Safety Walk Grip on Exterior Door Paddle Latches.	1	RRI
SIDE DOOR STEP			1	RRI
03-08-2000		(2) Step Well, Side Entry Increased Depth, Lower Grip, Upper Diamond Plate	1	RRI
03-08-3010		Stepwell Light LED, Whelen OS Mini, Clear (STANDARD)	1	RRI
WINDOWS			1	RRI

PART NO	S	DESCRIPTION	QTY	ID
03-09-0030		Module Window Requirements	1	RRI
03-09-1110		Window Side Entry Door, 18X18, Slider Standard Glass	1	RRI
03-09-1210		Window Rear Entry Doors, 18X24, Fixed Standard Glass	1	RRI
		MODULE TO CHASSIS MOUNTING SYSTEM	1	RRI
03-10-5000		Module to chassis mounting system-Light Duty I (10)	1	RRI
03-11-6000		Connecting Bellows, Type I	1	RRI
		REAR BUMPER AND REAR STEP CONSTRUCTION	1	RRI
03-12-1600	<	Rear Bumper Fixed (STANDARD)	1	RRI
		Fixed Rear Bumper Fixed 7"W Bumper with the selected option for bumper end pods on the ends and fixed 45" center Grip Strut Insert. (STANDARD).		
03-12-3020	< >	Bumper Pods, CPI Cast Aluminum w/RR Logo. (UM & PM)	1	RRI
		Cast Products Bumper Pods, High Polish Finish. Mounted on the outboard rear step bumper frame members. The CPI cast aluminum pod shall include a RR Logo embossed in the cast pattern on the step tread.		
		INSULATION	1	RRI
03-13-2220	< >	Whisper Quiet Sound Dampening/Thermal Insulation Package (UM & PM)	1	RRI
		Whisper Quiet - Sound Dampening/Thermal Insulation Package. (ULTRAMEDIC AND PROMEDIC)		
		Spray foam underbody insulation prior to undercoat application, full subfloor coverage where applicable. Includes curbside step well area.		
		ELECTROLYSIS PREVENTION	1	RRI
03-14-4000	<	Electrolysis Prevention, Fluid Film (STANDARD)	1	RRI
		Fluid Film is used at Every Point Where the Mounting Process has the Propensity to Break Paint (STANDARD)		
		COMBINATION RUB RAIL AND FENDER RING	1	RRI
03-15-2000	<	Crash Rail and Fender Ring (STANDARD)	1	RRI
		Extruded Black Rubber Crash Rail and Fender Ring - The lower body Rub Rail/Crash Rail and Fender Ring to be Black extruded rubber. The rubber rail will be snap-on mount with no fasteners. The extrusion that the rubber rail fastens to will be secured to the body with aluminum rivets for ease of replacement. The lower body crash rail and the transition to the Fender Ring will have Polished Aluminum end caps. The extrusion to accept multiple color inserts. (STANDARD)		
03-15-5510	<	Lighting LED Strip, Kinequip, In Standard Rubber Crash Rail	1	RRI
		Install horizontal LED rub rail lighting on fore and aft of each rear wheel well cutout on both sides of the module.		
		This does not include the fender rings.		
		LED Color: RED/WHITE/BLUE FLASHING FUNCTIONALITY: The RED/WHITE/BLUE LED's are to fast flash alternately RED then WHITE and will come on with 'Master Emergency' and also include a cut-out switch labeled 'RUB RAIL C/O' in the front switch panel. The cut-out switch will disable the RED/WHITE when alternate flashing. When placed in park the flashing RED/WHITE LED's will continue to flash as long as master emergency is enabled.		
		STEADY BURN FUNCTIONALITY: The WHITE LED's are to steady burn to act as courtesy/perimeter lighting when vehicle is in 'Park' and module power is 'On' for a period of 29 seconds and also include a switch labeled 'Ground Light' in the front switch panel to activate when vehicle is in 'Park' and module power is 'On'.		
		To also activate when a corresponding compartment door or entry door is opened and illuminate the ground area below the vehicle. - If the rear entry doors are open the rear most rub rail lights on both sides of the module will light. - If the #1 or #2 exterior compartment door is opened the forward street side rub rail		

PART NO	S	DESCRIPTION	QTY	ID
		will light.		
		- If the #4 compartment door is opened the rear street side rub rail will light.		
		- If the #6 compartment door is opened the rear curb side rub rail will light.		
		- If the curbside entry or the #8 exterior compartment door is opened the forward curb side rub rail will light.		
		When the vehicle is placed in gear the courtesy/perimeter lights will auto cut-out.		
		SPLASH GUARDS AND RUNNING BOARDS	1	RRI
03-16-1521		Running Boards Diamond Plate, Type I, 2017+ Ford (Standard)	1	RRI
03-16-1800	<	Mud Flaps Rear, Black w/ RR Logo (Standard)	1	RRI
		Heavy Duty Rubber Mud Flaps w/ RR Logo		
		- Heavy Duty Rubber Mud Flaps to be bolted to the wheel liner behind the rear duals with with 1/4" x 20 Stainless Steel bolts, washer and nylon locknut for ease of maintenance and repair		
		(STANDARD)		
03-17-1000	<	Drip Rails	1	RRI
		Polished Aluminum Drip Rails - Above All Doors, Entry and Compartment (Standard)		
03-18-1000	<	Wheel well liners	1	RRI
		Aluminum Wheelwell Liners - Extending to Bottom of Skirt (Standard)		
		CAB TO MODULE ACCESS	1	RRI
03-19-1100		Pass Thru Opening Type I	1	RRI
03-19-4900	>	Pass Thru Window, Type 1 Ford,GM or Dodge	1	RRI
		LICENSE PLATE HOLDER	1	RRI
03-20-00SR	X	Unit number placards, CS and SS	2	
03-20-0510	>	Rear License Holder Location C/S Above Rear Kickplate	1	RRI
		EXTERIOR COMPARTMENT CONSTRUCTION	1	RRI
04-01-0100		Exterior Compartment Construction, Light Duty	1	RRI
04-01-3000	<	Door Sill Protection, Stainless Steel. (STANDARD)	1	RRI
		Door Sill Protection - Install Stainless Steel sill protector on lower edge of all door frames to prevent paint damage. (STANDARD)		
		EXTERIOR COMPARTMENT DOORS	1	RRI
04-02-0100		Compartment Door Hidden Hinge, Seal on Door (UM)	1	RRI
04-02-0715	< >	Compartment Handles, Exterior TriMark 2015 Chrome/Black (UM)	1	RRI
		TriMark Two-Point Cast w/Polished Chrome Paddle Handle and Housing, Locking and Non-Locking, with floating cam - Mounted in CNC Cut Opening in Each Compartment Door Skin w/OEM Clamp Assembly.		
		(STANDARD ULTRAMEDIC)		
04-02-0741	< >	Compartment Handle, TriMark 2015 Chrome/Black, Street side, locking	1	RRI
		For single doors or Leading doors on the streetside.		
04-02-0751	< >	Compartment Handle, TriMark 2015 Chrome/Black, Curbside, locking	1	RRI
		For single doors or Leading doors on the curbside.		
04-02-0805	<	Compartment Door Locks 2015 TriMark	1	RRI
		Compartment Door Handle Manual Locks. - All doors shall incorporate double cut, non-directional tumbler assemblies that are keyed alike (STANDARD)		
04-02-1000		Compartment Door Nader Pin (STANDARD)	1	RRI
04-02-1200		Compartment Door Lubrication Door Handles and Latches (STANDARD)	1	RRI
04-02-1300		Compartment Door Reflectors (STANDARD)	1	RRI
04-02-1500		Magnetic Compartment Door Switches (STANDARD)	1	RRI
04-02-2010		Compartment Door Panel, Inner Diamond Plate (STANDARD)	1	RRI
04-02-2300		Compartment Door, Gas Struts (STANDARD)	1	RRI
04-02-2500		Compartment Door Panel Mounting Screws (STANDARD)	1	RRI

PART NO	S	DESCRIPTION	QTY	ID
04-03-0410	<	Compartment Light Locations Ultramedic Compartment Light Locations - Standard for Ultramedic (1) #1 Ceiling. 4" light (1) #1 Under O2 shelf (Surface Mount) 6" light with switch (2) #2 Wall above and below standard shelf. 4" light (2) #4 Wall above and below standard shelf. 4" light (1) #6 Ceiling.4" light (3) #8/Right Stack - One in each shelf section. 4" light NOTE: Must pick lights from menu. Any lights other than the standard 4" rnd grommet light must be picked ILOS and any additional locations must be picked as IATS.	1	RRI
04-03-1550	<	Door Open Indicators, (STANDARD VMUX) Door Open Indicators, - Magnetic Proximity Switches located at the top of the door between the jamb and the door frame will activate a door open indicator on the driver's control panel. The Vista display screen will include a digital layout with door open indicators for each module door and activate the corresponding Interior compartment light. NOTE- OPEN CAB DOOR WILL NOT BE SHOWN ON DISPLAY. (STANDARD)	1	RRI
04-03-2400		Compartment Lights LED, Flexible Strip, KineQuip EXTERIOR COMPARTMENT INTERIOR	1	RRI
04-04-1000	<	Exterior Compartment Interior Finish, Scorpion Rubberized Exterior Compartment Interior Scorpion Rubberized Liner Color Choice. Scorpion rubberized polyurethane coating applied to the surfaces of ALL exterior compartment walls and dividers. Does not include slide out battery tray or mounting angles. Battery Tray to be raw aluminum. NOTE: If there is not a slide out battery compartment in the order the #8.5 exterior compartment area will be Scorpion lined.	1	RRI
04-04-1003	<	Color = Black ALL COMPARTMENTS	1	RRI
04-05-0001	<	Exterior Compartment Shelving and Unistrut Standard All exterior shelving Unistrut shall be welded to the walls prior to any compartment wall finish. Where specified, exterior adjustable shelves shall be box pan formed of a minimum .125 inch Aluminum Diamond Plate and corners shall be welded. Shelves shall be infinitely adjustable, and securely mounted to heavy gauge aluminum Unistrut track. (Standard)	1	RRI
04-05-1000	<	Compartment Shelving Diamond Plate (STANDARD) Diamond Plate Exterior Compartment Shelving. (STANDARD)	1	RRI
04-06-0010	<	EXTERIOR COMPARTMENT #1 Electrical Storage Compartment #1 #1 Compartment Electrical Storage - Recessed into the bulkhead side of compartment #1 shall be an enclosed area for the installation of miscellaneous electrical components. The aluminum cover for this area to be installed with 'J' molding The 'J' molding to be full length of panel on bottom and inboard side. Outboard side of panel to be secured with mechanical fasteners. (STANDARD)	1	RRI
04-06-0300	< >	Compartment #1 Reduced Height Reduced Height of #1 Compartment or Upper Left #1 Cabinet - Reduce the height of the #1 compartment to accommodate an interior upper left #1 cabinet. Includes deletion of standard fixed shelf. See option 5.12.200 for upper left #1 cabinet.	1	RRI
04-06-SR01	X <	reduce the width of the #1 compartment to accommodate just a M cylinder 18 inche SR #2018048F reduce the width of the #1 compartment to accommodate just a M cylinder 18 inches	1	

PART NO	S	DESCRIPTION	QTY	ID
		wide This also modifies the action area counter, action area upper cabinets and sub-floor structure.		
		EXTERIOR COMPARTMENT #2		
04-07-0600	<	Compartment #2 Standard Configuration, (UM) #2 Compartment to be directly behind the #1 compartment and below the interior action area shelf on the street side of the module. Includes (1) adjustable shelf on Unistrut track. (STANDARD Ultramedic) SEE CUSTOM width	1 1	RRI RRI
04-07-0SR1	X <	Maximize the width of the #2 compartment SR #2018048F Maximize the width of the #2 compartment	1	
04-07-0SS1	X <	mounted SCBA bracets at a 45 degree angle in the # 2 compartment SR #2018048F mounted SCBA bracets at a 45 degree angle in the # 2 compartment on back wall both sides (reference sugarland design) Add fabricated angled mounting plates in the rear corners of the #2 exterior compartment for the installation of SCBA brackets. Does not include SCBA brackets.	1	
04-07-0ST1	X <	Helmet Hooks for Compt #2 (2) on #2 wall. (1) on #1 wall (1) on #3 wall between SCBA and door	4	
04-07-2615		Shelf Adjustable Compartment #2,Delete	1	RRI
		EXTERIOR COMPARTMENT #4		
04-09-3000	<	Compartment #4 3/4 height, Standard Configuration Full Height #4 Compartment streetside rear of module with Interior Upper left Cabinet - #4 Compartment to be full height to bottom of upper left #4 cabinet.	1 #4	RRI RRI
04-09-4505		Shelf Adjustable , Compartment #4, Standard	1	RRI
		EXTERIOR COMPARTMENT #6		
04-11-0600		Compartment #6 Standard Configuration (UM)	1	RRI
04-11-2000		Divider, Adjustable Compartment #6	1	RRI
04-11-4625	X <	add safety bar in back board compt 68 inches from floor of cabinet. Black scorpion coat	1	
04-11-4635	< >	Equipment Strap (1),Seat Belt Style, Metal Buckle-(Specify Location) (1) Seatbelt style strap with metal buckle. (Push button) Must pick quantity if more than one is needed. Location: Compt #6 for stairchair	1	RRI
04-11-8000		Exterior #6 Compartment Floor Matting "Turtle Tile", Black	1	RRI
04-11-SR01	X <	Reduce the depth of #6 compt SR #2018048F reduce the depth of the # 6 and notch the door to accomodate housing the stair chair (per mark schwartzbauer this can be done. The customer wants to maximize the over all aisle width of this truck	1	
04-11-SR02	X <	stair chair wheel guide in the # 6 compartment SR #2018048F stair chair wheel guide in the # 6 compartment (reference austin travis county units) B344091	1	
		EXTERIOR COMPARTMENT #8		
04-14-1400		Compartment #8 Full Height, "A" Style Configuration	1	RRI
		EXTERIOR COMPARTMENT #8.5		
04-15-2100		Compartment #8.5 Hinged Door Battery Box Configuration	1	RRI
	<	INTERIOR TRIM AND FEATURES		
		New Interior Trim - All cabinet and wall panel aluminum trim to be Gray anodized. (No Black trim to be used). All protective corner trim will be Opaque and will include a	1	RRI

PART NO	S	DESCRIPTION	QTY	ID
		matching domed end cap. (STANDARD)		
		INTERIOR ADJUSTABLE SHELVES	1	RRI
		INTERIOR TRIM	1	RRI
05-05-1000		Interior Trim Standard	1	RRI
		HEADLINER	1	RRI
05-06-1100		Ceiling Medical Device Rail (STANDARD)	1	RRI
05-06-1200		Headliner Vinyl Ceiling, No Seams (STANDARD)	1	RRI
05-06-1802		White LED Strip Lights, Ceiling Medical Device Rail. (UM & PM)	1	RRI
05-06-1902		Red/Amber LED Turn/Brake Strip Lights, Ceiling Medical Device Rail. (UM & PM)	1	RRI
		FLOORING	1	RRI
05-07-1000		Aluminum Floor/Wall Cove Moulding. (STANDARD)	1	RRI
05-07-1400		Stainless Steel Rear Threshold, 45 Degree Chamfered (STANDARD)	1	RRI
05-07-5000		Loncoin II Flecks Flooring Choice (STANDARD)	1	RRI
05-07-5003		Color 157 Moonstone	1	RRI
05-07-6100		Curbside Stainless Steel Threshold,4" wide,W/Safety Walk Anti-Skid Tape	1	RRI
		HEAD BUMPERS	1	RRI
		BACKRESTS	1	RRI
		Rear Entry Door Grab Bars	1	RRI
05-10-1307		Rear Entry Door Grab Bars "C" Bars Antimicrobial	1	RRI
05-10-1407		Side Entry Door Grab Bar "C" Bars Antimicrobial	1	RRI
05-10-1903		Ceiling Grab Rail Center 108" Anti-Microbial	1	RRI
05-10-7301	X <	(1) 18" grab bar, antimicrobial	1	
		mounted at a 45 degree angle mounted on the front work station on the step well side		
		PLASMA HANGER	1	RRI
05-11-4000		IV Hangers CPI #IV2008 (STANDARD)	1	RRI
05-11-4002		Quantity (2)	1	RRI
		INTERIOR STREETSIDE #1 LEFT STACK and BULKHEAD	1	RRI
05-12-0200	< >	Upper Bulkhead Cabinet Double Doors (STANDARD)	1	RRI
		Upper Bulkhead Electrical Cabinet, Double Doors		
		- Install double hinged Kydex Thermoplastic or multi-spec (picked in the proper section of work order) doors with locking latch on the right hand door and center mullion on the left hand door on the standard upper bulkhead electrical cabinet.		
		**will use multi-spec in misty gray for all walls that arent stainless. Also multi-spec on drawers and glove holders in doors		
		Must use M1 latches for CN 10 certification (STANDARD)		
05-12-0250	< >	Left Stack Storage Area #1. (STANDARD Ultramedic)	1	RRI
		Left Stack Radio/Inverter cabinet to include (1) adjustable shelf in upper section. Both sections shall have double solid aluminum, Kydex Thermoplastic or multi-spec (picked in the proper section of work order) covered doors with locking Latch on the upper doors and locking latch on the lower doors.		
		Must use M1 latches for CN 10 certification (standard Ultramedic)		
		INTERIOR STREETSIDE #2 ACTION AREA	1	RRI
	<	action area counter to be 60 inches		
05-13-0700		Medical Device Rail Action Area Wall	1	RRI
05-13-0802	<	Cabinets Upper Left U2 and U2.5, Std Configuration (UM) CN 10 Certified	1	RRI
		- (2) Cabinets over Action Area with sliding doors and restocking feature. The forward UL #2 and the rearward UL #2.5 cabinets to include (1) adjustable shelf in each cabinet. The attendant switch panel and environmental controls to be built into a separate 6" high section below the Upper Left #2.5 cabinet and tilted slightly down for ease of accessibility to the attendant.. (STANDARD Ultramedic, Promedic)		
05-13-2200	< >	Countertop Forward Action Area and Rear Monitor Area.	1	RRI
		action area counter to be 60 inches		

PART NO	S	DESCRIPTION	QTY	ID
05-13-2203		Avonite Black Ice, K3-7100	1	RRI
05-13-SR10	X <	u2.5 to be angled to house the knox medvault SR #2018048F	1	
		u2.5 to be angled to house the knox medvault (bigger size) reference austin but needs to be the larger Medvault 2 Does not include MedVault. ILOS		
INTERIOR STREETSIDE #3 CPR SEAT			1	RRI
05-14-0500	<	Streetside CPR Seat, Standard Configuration	1	RRI
		- The CPR seat shall include a flip up seat equipped with a gas strut hold open device and positive latch for securing the lid when closed. The CPR seat shall include a 2" foam seat and backrest, the upper and lower sections will be padded on both sides for added protection.		
05-14-0900	<	CPR Seat Lid Hold-Down	1	RRI
		CPR Seat Lid Hold-down - Install a Black Tri Mark recessed paddle latch, (1) under CPR seat lid.		
05-14-2550		Seat Belt, CPR Seat 6-Point-Change Notice 8-Compliant	1	RRI
05-14-3900	<	"U" Barrier Bar, Padded, 6 7/8 x 7 1/2, 1.5 inch SS, CPR Seat	1	RRI
		Mounted at the front of the CPR side seat vertically in line with the Padded head cushion on the "U2" cabinets.		
05-14-SR10	X <	Widen the Standard CPR seat to 40". SR #2018048F	1	
		Widen the Standard CPR seat to 40". Includes modifying upper cabinets.		
05-14-SS10	X <	pull out drawer to pull into the CPR seat area to SR #2018048F	1	
		pull out drawer to pull into the CPR seat area to 12 inches deep by 4 inches tall as wide as possible This will raise the counter tops in the action area and telemetry area. Drawer to have 12" non-locking slides. CN10 Certified 5.13.265.4		
INTERIOR STREETSIDE #4 REAR AREA			1	RRI
05-15-1020	<	Cabinet Upper Left U4, Standard Configuration-CN 10 Certified	1	RRI
		Upper left U4 cabinet with sliding polycarbonate doors with spring loaded latching handles, restocking feature with spring loaded exterior integral latch and (1) adjustable shelf.		
05-15-SR10	X <	Custom Upper Left U4, Angled, restocking SR #2018048F	1	
		Custom Upper Left U4, ANGLED, Restocking Cabinet. Custom Angled Upper left #4 Cabinet with sliding Lexan doors, restocking feature and (1) adjustable shelf. Exhaust vent in rear section. To be approx. 14" high x 7.50" deep in the forward section and extend out near rear door opening. THE CLOSE OUTS FOR THE WIRE HARNESSSES ARE TO BE ANGLED UP AT A 45 DEGREE ANGLE. THIS IS TO ACCOMMODATE THE MOUNTING OF 2.50"W X 30"L. BOTTOM EDGE LITE LIGHT RAIL. (SO.UL4.3R6148)		
05-15-SS10	X <	Double wall angled cabinet above rear counter top SR #2018048F	1	
		Double Wall ANGLED cabinet above rear counter top. To have C4 and C4.5 cabinets. Each to have sliding Lexan doors, restocking feature and (1) adjustable shelf in each. To be approx. 18" high x 7.50" deep in the forward section and extend out near rear door opening. Cabinet Shelves depth to be 6". The return on the rear portion of the shelf has to be bent downward to achieve this (see reference pictures on server).		

PART NO	S	DESCRIPTION	QTY	ID
		Above the cabinet is to have a space for routing wire harnesses. NOTE: All horizontal corners to have 'X' moulding and rubber protection. Maximize depth of shelves for customer's bins (SO.DWC.3R6148)		
INTERIOR CABINETS-SQUAD BENCH AREA			1	RRI
05-16-0100		Curbside Squad Bench Two Piece Hinged Lid	1	RRI
05-16-0300		Restraint Belts, Squad Bench Standard	1	RRI
05-16-0500		Medical Device Rail Squad Bench	1	RRI
05-16-0600		Latches, Lids Squad Bench Tri Mark , Standard	1	RRI
05-16-1015		Seat Belts, Squad Bench Two 6-Point belts Change Notice 8-COMPLIANT	1	RRI
05-16-SR10	X <	interior access in the #6 compartment to face the squad bench SR #2018048F interior access in the #6 compartment to face the squad bench CN10 Certified	1	
05-16-SS10	X <	custom workstation at head of squad bench SR #2018048F Cabinet at the head of the squad bench with counter top and (2) drawers. Drawers to open to aisle. Drawers to have 18" non-locking slides and be held closed with a locking latch. Drawers to be 12" wide x 18" deep. Drawer face to be solid aluminum and finished to match the interior of the module. Squad bench will not have back board carrying capabilities. custom medical device rail over the custom work station (1) 110 outlet (1) USB plug (1) O2 port Does not include any outlets, plugs or ports.	1	
05-16-ST10	X <	add a tip out for (2) spare D cylinders SR #2018048F add a tip out for (2) spare D cylinders in the front action cabinet tipping out into the step well This cabinet is not CN10 Certified. Must select FW 521 O2 holders seperately in QW.	1	
INTERIOR BIOHAZARD			1	RRI
05-17-1000	>	DELETE Standard Squad Bench "A" Bar Grab Bar	1	RRI
05-17-2000	>	Glove Butler(s)	1	RRI
05-17-20SR	X <	add glove butler to the rear entry doors SR #20161049F add glove butler to the rear entry doors (reinforce to keep the glove door flange from falling open when the rear doors are shut) Glove Box Storage, (2) Total, recessed in rear entry doors 58 (SO.GLOVE.1R6237) SR#2016321F This will be a fabricated glove box storage cabinet recessed into each of the lower rear entry door panels. Each cabinet to have a solid aluminum door with an oval cutout and a roller catch. This option does not include a Glove Butler. Reference Sales Drawings & #1R7253	2	
05-17-3000	< >	Drawer Waste and Sharps, Slide-out, Head of Squad Bench, 18" Slides The squad bench shall include a slide out combination Waste/Sharps storage drawer at head of squad bench, Supplied with a 5 quart Sharps container and an 8 quart Waste container. Face of slide out drawer to be stainless steel and will include a locking latch. Must use M1 latches for CN 10 certification See drawing for location exterior to be misty gray multi-spec	1	RRI
INTERIOR CURBSIDE RIGHT STACK STORAGE #8			1	RRI
05-18-SR10	X <	Custom cabinet, right stack Install a cabinet with aisle side access. Includes (2) doors hinged framed Lexan door and locking latch.	1	

PART NO	S	DESCRIPTION	QTY	ID
		Includes (1) adjustable shelf. Approx. 18" Wide x 24" high x 12" deep. Includes a 2 inch deep dead space for wire harnesses. SR #20161049F	2	
ATTENDANT SEAT				
05-19-5900		Attendant Seat EVS Vac Form, 3-Point Belt W/ Child Seat, Swivel Base	1	RRI
05-19-5908		Color Black	1	RRI
INTERIOR COLORS				
05-20-2000		Multi-Spec Interior Surfaces ILOS	1	RRI
05-20-2001		Color Misty Grey #6028,ILOS	1	RRI
05-20-5300	<	Upper Band Vinyl Color Cabinets and Stitched Cushions	1	RRI
		Upper Band Vinyl Color Choice for cabinets and stitched cushions.		
05-20-5326		Color Stratford Smoke SF-74	1	RRI
05-20-5500		Lower Band Vinyl Color Vacuum Formed Cushions	1	RRI
05-20-5502		Color Ash Gray	1	RRI
05-20-9850		Polycarbonate Color Choice	1	RRI
05-20-9851	<	Polycarbonate, Gray	1	RRI
		1/4" polycarbonate		
MISC. INTERIOR OPTIONS				
05-21-02SR	X <	(1) PD-4 Organizer (location TBD)	1	RRI
		SR #2018048F		
		Location must be approved by engineering. EACH IATS		
05-21-1320	<	Refrigerator Engel Model MD14F, 12V Portable	1	RRI
		Engle cooler DC power mounted to the floor behind the attendant seat and the action area. Run the wiring through the floor (no exposed wires)		
05-21-2001	X	Adjustable divider (1) interior cabinet	2	
05-21-2011	<	(1) additional adjustable dividers.	12	RRI
		U2, U4, C4, U8, U7 and U7.5.		
		NO MORE than .5" from bottom of shelf and/or cabinet		
05-21-4000		Interior Cabinet Lights, Kinequip LED Strip	1	RRI
05-21-4010		Upper Left Cabinets 2, 2.5 and 4	1	RRI
05-21-5000		Squad Bench & Lower Left, 4 Inch Brushed Stainless Kickpanels (STANDARD)	1	RRI
05-21-8700		Cabinet Latch Southco Lever Latch, Gray Locking-CN 10 Rated at 5lbs	1	RRI
05-21-8700		Cabinet Latch Southco Lever Latch, Gray Locking-CN 10 Rated at 5lbs	2	RRI
06-01-0100		General Wiring General Harness Standard	1	RRI
COMMUNICATION				
06-06-00SR	X <	Blinker Cameras for both dr and pass side cab	1	RRI
		SR #2018048R-1		
		blinker cameras (both driver side and passenger side) can this be wired to the hanscom rear view mirror camera		
		(1) blinker on each side, rear back up camera. no patient compt camera. rear view mirror monitor with audio		
		Hanscom HC-770619N with HC-201 (Right and left).		
06-06-0150	<	Antenna UHF/VHF (2) Prewire, Standard	1	RRI
		two RG58AU low loss cables installed from the two-way radio cabinet to the ceiling of the module. Accessible be removing an interior light in the patient compartment ceiling. The interior light shall include an etched plastic label identifying the plate as the antenna access point. The cables shall route from the module roof to the lower section of the left stack/radio cabinet and be of sufficient length to allow routing to the cab console as an alternate radio installation location.		
06-06-1600	<	Two Way Radio Routing Path Cab to Module. (STANDARD)	1	RRI
		prewire motorola Apex 6500 radio to the action area and the center console. Power and Ground		
06-06-1700		Two Way Radio Prewire, 12VDC Power and Ground (STANDARD)	1	RRI

PART NO	S	DESCRIPTION	QTY	ID
06-06-7600	<	Intercom Sigtronics Ultrasound Intercom System Sigtronics (2 headsets up front in cab) and (1) in rear in action area with one ear open and one closed ear	1	RRI
RADIO AND CLOCKS			1	RRI
07 ELECTRICAL 12 VOLT DC			1	RRI
07-00-SR00	X <	deutsch connect for eas of remount purposes SR #2018048F Electrical system connected to Chassis Via Deutche Connections. (SO-ECONN-361167) For ease of Remounting-102-PIN Deutsche connector to connect the module with the chassis	1	
07-01-0010	<	Crct Pwr Accs.,Ign/Shrline,1-20 amp 12VDC to 2 locs,W/O,PD9130 chrgr (1) 10 amp lead shall be coiled up behind the A./A panel for future use. (1) 10 amp lead shall be coiled up behind the drivers seat in the cab, for future use. Note: This code will be used when and additional battery charger has already been installed, the PD9130 will not be used with this option.	1	RRI
07-02-1000		Voltmeter Standard	1	RRI
07-02-1100		Alarm,Low Voltage,With Buzzer and Indicator,in cab console	1	RRI
07-03-2000		Ammeter for multiplex system	1	RRI
BATTERY SYSTEM			1	RRI
07-04-5305		Ignition Battery Shut off Timer, 5 minute, (Standard)	1	RRI
07-05-0400	<	Batteries Type I UM/PM, Ford or Dodge Ram (2) OEM (1) Additional,STD The two OEM batteries under the hood. One 735 CCA AC Delco additional battery shall be supplied by the manufacturer and located in the exterior compartment located below the right front ALS cabinet.	1	RRI
07-07-0500		Module Disconnect Multiplex System,	1	RRI
07-08-0100		Battery Ground	1	RRI
07-09-6000		Battery Charger Prewire only, 12V. (STANDARD)	1	RRI
07-10-1000		Power Outlets 12V, (2) Power Point Style, On with Ignition (STANDARD)	1	RRI
07-10-7200	<	Outlet, Dual USB Port, 5VDC, 2.1Amp output, Standard Located on the passenger side of the center console, per Electrical Engineering	1	RRI
07-10-7250	<	Outlet, Dual USB Port, 5VDC, 2.1Amp output, IATS Location : over SB cabinet / see drawing	1	RRI
FRONT CONSOLE			1	RRI
08-01-00SR	X <	Custom center console, black multi scorpion, ILOS SR #2018048F customer center console black multi scorpion lined to include radio cut outs, knox key secure, 3 radio cut outs, space for map books and computers, 110 V outlet, customer will provide drawings refernce austin Does not include Knox Secure or any outlets	1	
08-01-1605	<	Driver's Switch Panel/Radio Console VMUX, Standard SEE CUSTOM	1	RRI
08-02-1150		Driver's Control Panel V-Mux, Touch Screen	1	RRI
08-02-1151		Ford Chassis, Touch Screen, Double Dinn in dash mounted	1	RRI
ATTENDANT CONTROL PANEL			1	RRI
08-03-1150		Attendant's Control Panel V-MUX, Touch Screen, with bezel and USB charging port.	1	RRI
08-04-6002	<	Power Distribution Weldon V-MUX, Video Inputs (UM & PM) Weldon V-Mux Multiplex System w/7" LCD VGA Touch Screen on front and rear switch panels with V-Mux Nodes. Includes an O2 Regulator/Transducer Mounted in #1 Compartment. INCLUDES VIDEO INPUTS FOR BACK-UP CAMERA. NOTE: The battery shut-off circuit to remain on for 5 minutes after the ignition has been shut off.	1	RRI

PART NO	S	DESCRIPTION	QTY	ID
		Shutting off the ignition will activate a timer that will leave the batteries on for five minutes so that the module dome lights can be left on for patient unloading/vehicle restocking.		
		Clock - Digital, Rear Control Panel, V-Mux display		
		Electrical System 12V - V-MUX Multiplex System.		
		Voltmeter - Standard for V-Mux		
		Alarm, Low Voltage. Console, V-MUX Ammeter - for MULTIPLEX ELECTRIC SYSTEM. V-MUX Module		
		Disconnect - V-Mux Multiplex Electrical System		
08-04-6020		Joystick Control Weldon V-MUX with quick buttons	1	RRI
		EMERGENCY SYSTEMS Ford F-Series	1	RRI
		WARNING AUDIBLE SIREN, SPEAKERS, AIR HORNS	1	RRI
09-03-00SR	X <	Speakers (2) CPI "Through the bumper" speakers	1	
		SR #2018048F		
		Speakers - (2) CPI "Through the bumper" speakers, Ref. Code 9.3.5.0 ILOS speakers will be mounted in buckstop grill		
09-03-01SR	X <	open compartment/door buzzer to sound only when the truck is in gear not in park	1	
		SR #2018048F		
		open compartment/door buzzer to sound only when the truck is in gear not in park		
09-03-1010		Siren Electronic Whelen 295SLSA1	1	RRI
09-03-3090	< >	Air Horns Buell, 10" & 12" , Thru Bumper, Tank/Compressor, F-Series	1	RRI
		NO Air horns thru center of Front bumper type 1 FORDS per ECN1820		
		mounted in buckstop grill		
09-03-4032		Siren Electronic, Additional Whelen 'Howler', Ford F-Series	1	RRI
09-05-0200		Backup Alarm (STANDARD)	1	RRI
09-05-SR03	X <	Dimmer switch for all M series emergency lights	1	
		SR #20161044R-3		
		Provide dimmer switch for all Whelen M series emergency lights.		
09-06-0200		Emergency Sequencer/Load Manager (STANDARD)	1	RRI
09-50-1333	<	Visual Warning Front Upper (5) "Cool Bar" (2) Front Wall Configuration	1	RRI
		Must pick proper lighting from menu.		
		AUXILLARY EMERGENCY LIGHTS	1	RRI
09-70-4000	< >	Traffic Pre-Empt GTT Opticom Model 792H, Module Front Wall	1	RRI
		Located on top center of coolbar, above center light		
09-80-2110	< >	Warning Light Flasher Vanner 9860GCPE (STANDARD) Multiplex /PC System	1	RRI
		Vanner 9860GCPE Halogen/LED electronic flasher to power specified lights. Four flash Patterns avail.(Alternate flash, Triple burst, Quad burst, double burst.)		
		Standard will be dual Burst Flash unless otherwise noted.		
09-80-2300	X <	EEV InPower 4875P2 Flasher with alternating flash pattern	1	
		EEV - InPower 4875P2 Flasher with alternating flash pattern..		
		Install a InPower 4875P2 Programmable Electronic Flasher ILOS in the dead space area.		
		Flasher to be set to triple flash.		
		ALL WIRES TO BE LABELED LIGHTHEAD SPECIFIC AND ROUTED TO THE DEAD SPACE.		
		Install (4) terminal strips in the dead space area labeled Phase 1, Phase 1P, Phase 2, and Phase 2P.		
		Install (1) grounding stud near the 4875P2 flasher.		
		Connect all of the scan lock wires to grounding stud. All lights are to alternate and the		

PART NO	S	DESCRIPTION	QTY	ID
		model #900's are to alternate flash over/under. All forward facing White lights are to be 'On' in Primary mode only. Program flash pattern on light heads as follows: Model #500 Grill lights = Steady #25 Model #700 lights =Steady #14 Model #900 lights = Steady/Steady Install a relay near the flasher for an auto PARK cutout circuit. Label this relay 'Park Cut Out'.		
		NOTE: If the front fender intersection lights are ordered with split colors then the light head will be wired with constant power and set lighthouse to Comet flash alternating #3 flash pattern and if there are white LED's they will be 'On' in Primary mode only.		
09-80-3300	<	Emergency Flashers Set to KKK-A-1822F Flash Pattern (STANDARD) Can we make sure there is a "stutter" when brake pedal is depressed in rear brake lights??	1	RRI
09-95-1505	<	Whelen M9 LED, w/Chrome Flange RED / Clear Lens (Internal Flasher) ILOS	8	RRI
09-95-1509	<	Whelen M9 LED, w/Chrome Flange RED/BLUE Split Clear Lens (Internal Flasher) IATS	2	RRI
09-95-15SR	X <	MV9 lights on angled portion of the coolbar SR #2018048F MV9 lights on angled portion of the coolbar (clear lens) wire to one separate switch on center console to operate both scene lights on coolbar simultaneously Whelen M9V2*C with M9FB chrome flange. Must specify color. PAIR IATS	1	
09-95-1604	< >	Whelen M9 LED, w/Chrome Flange WHITE (External Flasher) ILOS, front center of coolbar	1	RRI
09-95-2407	<	Whelen M7 LED AMBER , Clear Lens (Internal Flasher) ILOS, Center rear	1	RRI
09-95-4201	<	Whelen 500 LIN6 Super LED RED, RED Lens ILOS Lights are to lay FLAT on grill and fender. NO housings...	4	RRI
		EXTERIOR AUTOMOTIVE LIGHTING		
10-01-00SS	X <	m2 rear amber lights for rear arrow stick SR #2018048F M2AC with M2FB chrome flange and M2FC TACTL Control head only. (6) Whelen M2AC Amber lights with M2FC chrome flange located above rear doors. Lights to be controlled by a Whelen TACTL5 Control Head and used as a traffic advisor. IATS	1 1	RRI
10-01-01SR	X <	Whelen OS Mini lights to in the lower right hand corner or rear facing doors fla SR #2018048F Whelen OS Mini lights to in the lower right hand corner or rear facing doors flashing red (ALL rear facing doors) Whelen 0SR00FCR EACH IATS	6	

PART NO	S	DESCRIPTION	QTY	ID
10-01-1050	<	Tail Lights, Brake/Turn Whelen M6-Series LED, Must Pick Flng Must pick housings or flanges. CHROME	1	RRI
10-01-1240	<	Back-up Lights Whelen M6-Series LED Rear, Must Pick Flng New Code	1	RRI
10-01-2010		Marker/Clearance Lights, Front Whelen OS Mini LED, Amber	1	RRI
10-01-2110		Marker/Clearance Lights, Side and Rear Whelen OS Mini LED, Red/Amber	1	RRI
10-01-3002	<	Chrome Flange,(1) Whelen M6 (Standard M6) Pick Quantity	6	RRI
10-01-5020	<	Outboard Rear Flashers, Wired to OEM Brake Lights (STANDARD) Rear corner lights are to be warning ONLY, NO BRAKES!	1	RRI
10-01-7300		Front Turn Whelen M6-Series LED Amber Arrow w/Flange	1	RRI
10-01-SR00	X <	rear chevron lighting (newest generation) SR #2018048F Rear Panels Chevron Lights -Angled - Kinequip strip lights approx. 12" in length with extruded channel. #KFA-RR-CRA-1. Includes Chevron flasher is KFA-CIO-01 for each group of (5) chevron lights.. Punch slots in the rear body panel to accommodate. LED colors will be combination Red/Amber. RR to laser cut mirrored S/S cover panels. These panels will be shipped loose if rear chevrons are not in the work order. This feature is similar to the flashing rub rail lights. Requires (2) flasher modules. The Top, middle, and Lower angled lights are to be solid RED LED's only when the OEM brakes are applied. This will over ride the emergency light function. This feature also applies when not in emergency mode. The (2) angled light above and below the center angled light are to be flash AMBER LED's only when the corresponding OEM turn signals are applied. This will over ride the emergency light function. This feature also applies when not in emergency mode. Red and Amber LED's are to be wired to master emergency lights and alternate Red then Amber. Chevron strip lights to be centered in Chevron stripes.	1	RRI
FLOOD AND LOAD SYSTEMS			1	RRI
10-02-00SR	X <	Pioneer side scene lights, ILOS SR #2018048F Whelen PFH2B Dual Panel Pioneer Plus Floodlight (Replaces PFP2) with chrome housing and PBH203B Semi-Recess Housing with chrome Flange. EACH ILOS	2	
10-02-2040		Rear Load Lights (2) Whelen M7 Series Super LED, Gradient Scene Light	2	RRI
10-02-3010		Lighting Operation Side Scene, Rear Load and Back-Up Lights, Standard	1	RRI
Cab Entry Lighting			1	RRI
INTERIOR LIGHTING CEILING			1	RRI
11-01-1400		Dome Lights Kinequipe 8" Round LED	1	RRI
11-01-8015		Floor Lighting LED Blue	1	RRI
11-01-9000		Timer 15 minute-Restocking (STANDARD)	1	RRI
11-01-90SR	X <	relocate timer switch to the front wall of the workstation facing the step well SR #2018048F relocate timer switch to the front wall of the workstation facing the step well area	1	
SPOTLIGHTS / HANDHELD LIGHTS			1	RRI
11-02-1000	<	Handheld Spotlight Sho-Me 200,000 CP DO NOT HARDWIRE	1	RRI

PART NO	S	DESCRIPTION	QTY	ID
		ATTENDANT LIGHT	1	RRI
11-03-00SR	X <	Additional Attendant Light under U8 cabinet, IATS SR #2018048R-1 LED strip light under the U8 cabinet Need an additional LED strip light under the U8 cabinet that will be in place of the RF stack. White LED Strip Light - Kinequip - Under U8 Cabinet - The LED light strip shall be mounted in an anodized aluminum channel on the bottom surface of the cabinet close to the wall. This light will be controlled with an On/Off switch on the rear switch panel. 11.3.8.1	1	
11-03-1010		Attendant Light 6" x 14" Diffusion Plate Light (Standard)	1	RRI
		SHORELINE INLET	1	RRI
12-01-00SR	X <	20 amp and 30 amp shoreline angled housing and paint to match SR #2018048F 20 amp and 30 amp shoreline angled housing and paint to match Does not include shoreline inlets. Must select shorelines seperately	1	
12-01-5400		Shore Inlet Kussmaul Super Auto-Eject, 20Amp	1	RRI
12-01-5702		Kussmaul, Eject, Cover, 30Amp, Red	1	RRI
12-01-5800		Additional Kussmaul Super Auto-Eject, 30Amp	1	RRI
12-01-6300		Kussmaul, Eject,Cover,15 or 20A,Red	1	RRI
12-02-0200		Receptacles, Interior 110V-15A (1) Action Wall, (1) Right Stack	1	RRI
12-02-2052	<	Receptacles, Interior (1) Additional 110V-15A, Over Squad Bench Above cabinet at head of SB	1	RRI
12-02-2100	< >	Receptacles, Interior (1) Additional 110V-15A, Custom Location (each) L8	1	RRI
		POWER SUPPLY 110VAC	1	RRI
12-03-1110		Inverter Charger Vanner 1050W, Indicator on Console	1	RRI
		ENVIROMENTAL CLIMATE CONTROL SYSTEM	1	RRI
13-01-00SR	X <	relocate HVAC over the #1 compartment SR #2018048F Relocate the HVAC to cabinet above the #1 compartment. The Heat A/C unit to be relocated to the street side of the module. The conditioned air to be ducted directly to a plenum that runs the entire length of the module and will include (6) adjustable vents that will evenly distribute the air flow. The interior of the plenum to be completely insulated with a reflective barrier. This option includes modifying the ceiling structure to accommodate air flow down the street side of the module.	1	
13-01-01SR	X <	Upper left #1 cabinet to house the HVAC SR #2018048F Upper left #1 cabinet to house the HVAC. There shall be a cabinet above the #1 compartment to house the HVAC unit. This cabinet is to have (2) stainless steel access panels. These panels will be punched to provide venting for the HVAC return air. There shall be an interior access panel to the power distribution area that will be hidden by this cabinet. There shall be a heat A/C unit located above the #1 compartment.	1	
13-01-1200		HVAC Central Air Flow Discharge (UM & PM)	1	RRI
13-01-2000		Climate Control Standard (UM & PM)	1	RRI
13-02-0100		Exhaust Fan 100 CFM Standard Location	1	RRI
13-02-5611	>	HVAC Aux Front Wall COOLBAR Hoseline, Ford F-series MULTIPLEX	1	RRI
13-02-5702	<	Cover,Cool Bar, (5) M9 Series lights Drawing # 303347 (5) M9 series lights only. Note: Will be painted same color as the mount location on box front.	1	RRI

PART NO	S	DESCRIPTION	QTY	ID
13-03-1000		Return Air System	1	RRI
13-03-2000		Return Air Central Plenum	1	RRI
13-03-3000	<	Heat /AC Cabinet	1	RRI
		SEE CUSTOM LOCATION		
COT MOUNTING PROVISIONS				
14-01-1010		Cot Mounting Hardware	1	RRI
14-01-1110		Post & Wheel Cups None (STANDARD)	1	RRI
14-01-1210		Safety Hook Ship Loose	1	RRI
14-01-1230		Safety Hook Stryker with bolts, Shipped Loose	1	RRI
14-01-1623	<	Stryker Power Load, No Wheel guide Change Notice 8-COMPLIANT	1	RRI
		includes constant hot power supply for battery charging.		
14-01-3097		Center Mount	1	RRI
OXYGEN AND AIR SYSTEMS				
14-02-0100		Oxygen System Multiplex	1	RRI
14-02-1000		O2 Cylinder Wrench (STANDARD)	1	RRI
14-02-2000		O2 Cylinder Bracket Zico #QR-MV (STANDARD)	1	RRI
14-02-3000		O2 Control Electric with Manual Bypass on Action Wall. (STANDARD)	1	RRI
14-02-4000		O2 Outlets Ohio Style, (2) Action Wall, (1) Squad Bench (STANDARD)	1	RRI
14-02-6120	< >	O2 Cylinder Holder (2) FW-521 Universal	1	RRI
		Tip out at AA cabinet		
14-02-9020	<	SCBA, (2) Bracket Installed Exterior Compartment, Zico Brkt # UN-6-30-3-SF Compt #2	1	RRI
VACUUM SYSTEM				
14-03-1010	< >	Suction System SSCOR On-Board (STANDARD)	1	RRI
		Conforms to J3043 requirements		
MISC MEDICAL				
14-04-00SR	X <	technimount LifePak 15 mount	1	RRI
		SR #2018048F 210-00-1 PC15 - Bracket Pro Serie 35 / Physio Control LP15 Complete assembly support includes standard anodized surface base, support device section, hardware and instruction EACH IATS		
14-04-01SR	X <	Knox MedVault, 5200 series	1	
		Mounted at head of SB in custom cabinet - see drawing SR #2018048R-1 Knox Med Vault 5200 series, mounted in angled cabinet, part of U2.5 Knox 5201 DrugBox, Recessed mount, Light Bar, Ethernet Port, Back Antenna Jack, Rubber Ducky Antenna. Does not include admin software. You must include your customer's "PS" number from Knox on your work order. Without it, we CANNOT order the MedVault. If your customer doesn't have a "PS" number, have them contact Knox and register with them. http://www.knoxbox.com/store/registerdept.cfm		
14-04-1000		Fire Extinguisher 5# (ABC) w/ Mounting Bracket. (STANDARD)	1	RRI
14-04-SR03	X <	1 knox key secure 3b with strobe to be keyed for FMFD	1	
		SR #20161044R-3		
		1 knox key secure 3b with blue strobe to be keyed for FMFD		
		2600 KeySecure® 3b USB with Blue Strobe, 2651, to be keyed for customer.		
		Located behind the passenger seat on the floor close to the center console.		
		This does not include modifying a cabinet for installation. This does not include a cabinet if required for installation		

PART NO	S	DESCRIPTION	QTY	ID
		PAINT AND FINISH		
15-00-0100		Road Rescue Paint Process Standard	1	RRI
15-00-SR00	X <	black scorpion line the rear kick plate and the front stone guards	1	
		black scorpion line the rear kick plate and the front stone guards (like city of corinth). Also do the running boards		
15-00-SR01	X <	Custom paint scheme, ILOS SR #2018048F Module to be painted black from the top down 12". Includes roof and roof radius. Select pinstripe seperately in QW. This does not include painting the chassis.	1	
15-01-2020	< >	Module and Cab Lower Half, Different Color, No Jambas Note: Must state color with paint code and request a paint spray-out for approval.	1	RRI
		FOR A TYPE 1 THE CAB INSERT MUST MATCH THE AREA THAT IT IS INSERTED INTO		
15-01-9810	<	Upper Paint Color Note: Must state color with paint code and request a paint spray-out for approval.	1	RRI
15-01-9820	<	Lower Paint Color Note: Must state color with paint code and request a paint spray-out for approval.	1	RRI
15-01-9902	<	Color Red FLNA30573 Note: Must request a paint spray-out for approval.	1	RRI
15-01-9999	<	Color CUSTOM, Specify Color Note: Must request a paint spray-out for approval.	1	RRI
		GRAPHICS AND LETTERING		
15-02-80SR	X <	Custom lettering/graphics Need layout, colors, sizing of graphics/letters for pricing	1	RRI
		SR #2018200F Custom lettering/graphics - exact design TBD by customer Lettering, stripes and badges and window perfs priced per photos submitted. This will be done by 24/7. If anything changes you will be required to submit a new SR listing exactly what you want.		
15-02-80SS	X <	ADD web perf to side and rear entry door windows SEE SR #2018200F Custom lettering/graphics	3	
15-02-80ST	X <	Custom rear chevron SR #2018200F Custom rear chevrons - black and red with gold seperating the colors Done by 24/7	1	
15-03-3900		RR Badge Logos (STANDARD)	1	RRI
15-03-4000		RR Logos and Model Name (STANDARD)	1	RRI
15-03-4001		Ultramedic Black Logos	1	RRI
15-04-1000		Nomenclature Plaques. DIESEL. (STANDARD)	1	RRI
		16 REFERENCES AND STANDARDS		
16-01-0200		Owner's Manual (STANDARD)	1	RRI
ZZ-ZZ-0A00	<	Indemnification Statement The purchaser agrees to defend, indemnify and hold Rev Ambulance Group harmless from any claims, costs (including actual attorneys' fees), damages and liabilities caused in whole or in part by any alteration or modification of, or changes or additions to the purchased products OR use of product for purposes it was not designed or intended for.	1	RRI

